

TYRES

Product group	Tyres	
Item number	12500388	
Valid tyre size	280 / 60 - 10	
LI / SI / PR	88 F, 6 PR	
TL/TT	TL	
Brand	Carlstar	
Tread pattern	All Trail II	



Notes and features

- The Carlisle All Trail was specially designed for use on hard surfaces.
- Its low, wide tread pattern makes the vehicle very stable.
- The uniquely firm tread compound provides a very good ride comfort.
- Its rubber compound makes the tyre very durable and provides outstanding handling characteristics on pavement, concrete and compacted soil.



Technical Informations

Item number	12500388
EAN	5999110804569
Valid tyre size	280 / 60 - 10
Alternative size 1	23x11.00-10
LI / SI / PR	88 F, 6 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	All Trail II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	9,00
Recommended rim size	9.0
Permitted rim size	8.0, 8.5
Maximum air pressure [bar].	2,34
Section width (mm)	277
Outer diameter of tyre [mm].	597
Stat. radius (SLR) [mm]	266
Rolling circumference [mm].	1771
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
88 F	560	80		2,34	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.