

## **TYRES**

Product group	Tyres
Item number	12500398
Valid tyre size	240 / 75 - 10
LI / SI / PR	89 A8, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	All Trail II



## Notes and features

- The Carlisle All Trail was specially designed for use on hard surfaces.
- Its low, wide tread pattern makes the vehicle very stable.
- The uniquely firm tread compound provides a very good ride comfort.
- Its rubber compound makes the tyre very durable and provides outstanding handling characteristics on pavement, concrete and compacted soil.



## **Technical Informations**

Item number	12500398
EAN	5999110800646
Valid tyre size	240 / 75 - 10
Alternative size 1	24x9.50-10
LI / SI / PR	89 A8, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	All Trail II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,60
Recommended rim size	8.0
Permitted rim size	7.5, 7.75, 8.5
Maximum air pressure [bar].	1,52
Section width (mm)	241
Outer diameter of tyre [mm].	610
Stat. radius (SLR) [mm]	272
Rolling circumference [mm].	1811
Tread depth (mm)	11,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
89 A8	560	40		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.