

TYRES

Product group	Tyres	
Item number	12500408	
Valid tyre size	255 / 50 - 10	
LI / SI / PR	68 F, 4 PR	
TL/TT	TL	
Brand	Carlisle	
Tread pattern	All Trail II	



Notes and features

- The Carlisle All Trail was specially designed for use on hard surfaces.
- Its low, wide tread pattern makes the vehicle very stable.
- The uniquely firm tread compound provides a very good ride comfort.
- Its rubber compound makes the tyre very durable and provides outstanding handling characteristics on pavement, concrete and compacted soil.



Technical Informations

Item number	12500408
EAN	5999110804491
Valid tyre size	255 / 50 - 10
Alternative size 1	20x10.00-10
LI / SI / PR	68 F, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	All Trail II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	6,30
Recommended rim size	6.0
Permitted rim size	7.5, 8.0, 8.5
Maximum air pressure [bar].	1,52
Section width (mm)	208
Outer diameter of tyre [mm].	516
Stat. radius (SLR) [mm]	230
Rolling circumference [mm].	1534
Tread depth (mm)	11,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
68 F	315	80		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.