Bohnenkamp Moving Professionals

17.11.2024

TYRES

Product group	Tyres	
Item number	12500413	
Valid tyre size	305 / 60 - 10	
LI / SI / PR	99 A4 / 93 A8, 4 PR	
TL/TT	TL	
Brand	Carlstar	
Tread pattern	Turf Trac R/S	



Notes and features

- Lawn tyre for all kinds of devices for professional lawn and landscape maintenance.
- Wide range of applications from zero-turn rotary mowers to utility vehicles.
- Tread design effectively protects green spaces.
- High tread depth guarantees longevity.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500413
EAN	5999110834542
Valid tyre size	305 / 60 - 10
Alternative size 1	24x12.00-10
LI / SI / PR	99 A4 / 93 A8, 4 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	Turf Trac R/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,40
Recommended rim size	7.75
Permitted rim size	8.0, 9.0, 9.5, 10.0
Maximum air pressure [bar].	1,40
Section width (mm)	302
Outer diameter of tyre [mm].	619
Stat. radius (SLR) [mm]	275
Rolling circumference [mm].	1835
Tread depth (mm)	8,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
99 A4	775	20		1,40	
93 A8	650	40		1,40	

17.11.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.