

TYRES

Product group	Tyres	
Item number	12500490	
Valid tyre size	215 / 60 - 12	
LI / SI / PR	84 A4 / 80 A6, 4 PR	
TL/TT	TL	
Brand	Carlisle	
Tread pattern	Multi Trac C/S	



Notes and features

- Tyre for professional use on lawns, gardens and golf courses.
- Durable rubber compound in conjunction with deep tread blocks.
- Tread pattern optimised for stability and traction.



Technical Informations

Item number	12500490
EAN	5999110800240
Valid tyre size	215 / 60 - 12
Alternative size 1	23x8.50-12
LI / SI / PR	84 A4 / 80 A6, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Multi Trac C/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,20
Recommended rim size	7.00
Permitted rim size	6.0, 6.5
Maximum air pressure [bar].	1,52
Section width (mm)	216
Outer diameter of tyre [mm].	563
Stat. radius (SLR) [mm]	252
Rolling circumference [mm].	1683
Tread depth (mm)	9,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
84 A4	500	20		1,50	
80 A6	450	30		1,52	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.