Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	12500495
Valid tyre size	23 x 8.50 - 12
LI / SI / PR	84 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Turf Master



Notes and features

- Tyre for professional use on lawns, gardens and golf • courses.
- Durable rubber compound in conjunction with deep tread . blocks.
- Tread pattern optimised for stability and traction. •

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500495
EAN	5999110802534
Valid tyre size	23 x 8.50 - 12
Alternative size 1	220/65-12
LI / SI / PR	84 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Turf Master
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,10
Recommended rim size	7.00
Permitted rim size	6.0, 6.5, 7.00I, 7JA
Maximum air pressure [bar].	1,52
Section width (mm)	213
Outer diameter of tyre [mm].	581
Stat. radius (SLR) [mm]	260
Rolling circumference [mm].	1735
Tread depth (mm)	8,6
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
84 A4	500	20		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.