

TYRES

Product group	Tyres
Item number	12500537
Valid tyre size	240 / 65 - 12
LI / SI / PR	93 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Multi Trac C/S



Notes and features

- Tyre for professional use on lawns, gardens and golf courses.
- Durable rubber compound in conjunction with deep tread blocks.
- Tread pattern optimised for stability and traction.



Technical Informations

Item number	12500537
EAN	5999110802893
Valid tyre size	240 / 65 - 12
Alternative size 1	24x9.50-12
LI / SI / PR	93 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Multi Trac C/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,80
Recommended rim size	7.00
Permitted rim size	7.00I, 7JA, 8.50, 8.50JA
Maximum air pressure [bar].	1,50
Section width (mm)	241
Outer diameter of tyre [mm].	610
Stat. radius (SLR) [mm]	273
Rolling circumference [mm].	1819
Tread depth (mm)	9,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
93 A4	650	20		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.