

TYRES

Product group	Tyres	
Item number	12500548	
Valid tyre size	255 / 65 R 12	
LI / SI / PR	51 M, 8 PR	
TL/TT	TL	
Brand	Carlisle	
Tread pattern	Dura Trail	



Notes and features

- The Carlisle Dura Trail is an ATV tyre for a variety of surfaces such as packed ground, desert sand, rocky to medium-hard terrain.
- Around the tyre shoulder running studs and an extremely deep rim protection protect the tyre from injury.
- The radial carcass, the robust rubber compound and overlapping tread blocks ensure driving comfort, slow wear and a long service life.
- The strongly protruding lugs guarantee a good grip, even with incipient wear.



Technical Informations

Item number	12500548
EAN	5999110836157
Valid tyre size	255 / 65 R 12
Alternative size 1	25x10.00R12
LI / SI / PR	51 M, 8 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Dura Trail
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	14,00
Recommended rim size	8.0
Permitted rim size	6.0, 6.5, 7.0, 7.5, 8.5
Maximum air pressure [bar].	1,40
Section width (mm)	261
Outer diameter of tyre [mm].	651
Rolling circumference [mm].	1952
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
51 M	195	130		1,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.