

TYRES

Product group	Tyres
Item number	12500560
Valid tyre size	360 / 50 - 12
LI / SI / PR	107 A4, 4 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	Ultra Trac



Notes and features

- Special tyre for professional lawn and landscape maintenance.
- Offers very good flotation properties due to a flat contact area and reduced tread gaps.
- Low soil pressure and good traction at the same time.



Technical Informations

Item number	12500560
EAN	5999110802329
Valid tyre size	360 / 50 - 12
Alternative size 1	26.5x14.00-12
LI / SI / PR	107 A4, 4 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	Ultra Trac
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	15,10
Recommended rim size	10.50
Permitted rim size	11.0, 12.0
Maximum air pressure [bar].	1,24
Section width (mm)	366
Outer diameter of tyre [mm].	673
Stat. radius (SLR) [mm]	299
Rolling circumference [mm].	1992
Tread depth (mm)	6,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
107 A4	975	20		1,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.