

TYRES

Product group	Tyres
Item number	12500561
Valid tyre size	205 / 80 R 12
LI / SI / PR	68 F, 6 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	A.C.T. HD



Notes and features

- The Carlisle A.C.T. is an ATV radial tyre for particularly rough terrain with soft to medium-hard ground conditions.
- The radial casing compensates for hazards and path damage and provides high traction and ride comfort.
- The open tread pattern with high tread depth provides good self-cleaning and grip on muddy trails.
- The strong sidewall makes the tyre particularly puncture-proof.
- Tyres in HD model (Heavy Duty) have an even stronger casing to enable higher inflation pressures and loading capacities.

Technical Informations

Item number	12500561
EAN	5999110804422
Valid tyre size	205 / 80 R 12
Alternative size 1	25x8.00R12
LI / SI / PR	68 F, 6 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	A.C.T. HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	9,50
Recommended rim size	6.5
Permitted rim size	6.0, 7.0
Maximum air pressure [bar].	1,24
Section width (mm)	196
Outer diameter of tyre [mm].	658
Stat. radius (SLR) [mm]	296
Rolling circumference [mm].	1975
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
68 F	315	80		1,20	