

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 12500563 |
| Valid tyre size | 205 / 85 R 12 |
| LI / SI / PR | 46 F, 4 PR |
| TL/TT | TL |
| Brand | Carlisle |
| Tread pattern | A.C.T. |



Notes and features

- The Carlisle A.C.T. is an ATV radial tyre for particularly rough terrain with soft to medium-hard ground conditions.
- The radial casing compensates for hazards and path damage and provides high traction and ride comfort.
- The open tread pattern with high tread depth provides good self-cleaning and grip on muddy trails.
- The strong sidewall makes the tyre particularly puncture-proof.
- Tyres in HD model (Heavy Duty) have an even stronger casing to enable higher inflation pressures and loading capacities.

Technical Informations

| | |
|------------------------------|-------------------------|
| Item number | 12500563 |
| EAN | 5999110800578 |
| Valid tyre size | 205 / 85 R 12 |
| Alternative size 1 | 26x8.00R12 |
| LI / SI / PR | 46 F, 4 PR |
| TL/TT | TL |
| Brand | Carlisle |
| Tread pattern | A.C.T. |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 75 |
| Nettogewicht [kg] (gültig) | 7,60 |
| Recommended rim size | 6.5 |
| Permitted rim size | 4.5, 5.0, 5.5, 6.0, 7.0 |
| Maximum air pressure [bar]. | 0,70 |
| Section width (mm) | 201 |
| Outer diameter of tyre [mm]. | 668 |
| Stat. radius (SLR) [mm] | 300 |
| Rolling circumference [mm]. | 2000 |
| Tread depth (mm) | 19,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 46 F | 170 | 80 | | 0,70 | |