Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	12500565
Valid tyre size	205 / 80 R 12
LI / SI / PR	43 N, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Pavemaster



Notes and features

- The Carlisle Pavemaster is a tyre for ATVs and SxS vehicles for use on paved paths and asphalted roads.
- The specially designed, flatter tyre centre provides ideal stability, especially on these surfaces.
- Wide spaces between tread blocks on the rounded tyre shoulder and the high tread depth guarantee traction, good riding and steering characteristics and self-cleaning on softer ground.

Bohnenkamp Moving Professionals

Technical Informations

lite we we we have	10500505
Item number	12500565
EAN	5999110833132
Valid tyre size	205 / 80 R 12
Alternative size 1	25x8.00R12
LI / SI / PR	43 N, 6 PR
TL/TT	ть
Brand	Carlisle
Tread pattern	Pavemaster
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	10,20
Recommended rim size	6.0
Permitted rim size	6.5, 7.0
Maximum air pressure [bar].	2,80
Section width (mm)	198
Outer diameter of tyre [mm].	640
Stat. radius (SLR) [mm]	287
Rolling circumference [mm].	1914
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
43 N	155	140		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.