

TYRES

Product group	Tyres
Item number	12500566
Valid tyre size	255 / 65 R 12
LI / SI / PR	50 N, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Pavemaster



Notes and features

- The Carlisle Pavemaster is a tyre for ATVs and SxS vehicles for use on paved paths and asphalted roads.
- The specially designed, flatter tyre centre provides ideal stability, especially on these surfaces.
- Wide spaces between tread blocks on the rounded tyre shoulder and the high tread depth guarantee traction, good riding and steering characteristics and self-cleaning on softer ground.

Technical Informations

Item number	12500566
EAN	5999110833149
Valid tyre size	255 / 65 R 12
Alternative size 1	25x10.00R12
LI / SI / PR	50 N, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Pavemaster
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	11,60
Recommended rim size	8.0
Permitted rim size	6.0, 7.0, 7.5, 8.5
Maximum air pressure [bar].	2,80
Section width (mm)	246
Outer diameter of tyre [mm].	648
Stat. radius (SLR) [mm]	291
Rolling circumference [mm].	1938
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
50 N	190	140		2,80	
	810	40		2,80	