

TYRES

Product group	Tyres
Item number	12500572
Valid tyre size	205 / 90 B 12
LI / SI / PR	49 M, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	A.C.T. HD



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The Carlisle A.C.T. is an ATV radial tyre for particularly rough terrain with soft to medium-hard ground conditions.
- The radial casing compensates for hazards and path damage and provides high traction and ride comfort.
- The open tread pattern with high tread depth provides good self-cleaning and grip on muddy trails.
- The strong sidewall makes the tyre particularly puncture-proof.
- Tyres in HD model (Heavy Duty) have an even stronger casing to enable higher inflation pressures and loading capacities.

Technical Informations

Item number	12500572
EAN	5999110835693
Valid tyre size	205 / 90 B 12
Alternative size 1	26x8.00-12
LI / SI / PR	49 M, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	A.C.T. HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	9,90
Recommended rim size	6.5
Permitted rim size	6.0
Maximum air pressure [bar].	1,50
Section width (mm)	208
Outer diameter of tyre [mm].	663
Stat. radius (SLR) [mm]	300
Rolling circumference [mm].	1998
Tread depth (mm)	26,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
49 M	185	130		1,50	