Bohnenkamp Moving Professionals

17.11.2024

TYRES

Product group	Tyres	
Item number	12500578	
Valid tyre size	255 / 70 B 12	
LI / SI / PR	56 M, 6 PR	
TL/TT	TL	
Brand	Carlstar	
Tread pattern	A.C.T. HD	



Notes and features

- The Carlisle A.C.T. is an ATV radial tyre for particularly rough terrain with soft to medium-hard ground conditions.
- The radial casing compensates for hazards and path damage and provides high traction and ride comfort.
- The open tread pattern with high tread depth provides good self-cleaning and grip on muddy trails.
- The strong sidewall makes the tyre particularly punctureproof.
- Tyres in HD model (Heavy Duty) have an even stronger casing to enable higher inflation pressures and loading capacities.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500578
EAN	5999110835709
Valid tyre size	255 / 70 B 12
Alternative size 1	26x10.00-12
LI / SI / PR	56 M, 6 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	A.C.T. HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	12,40
Recommended rim size	8.00
Permitted rim size	7.0, 7.5, 8.5
Maximum air pressure [bar].	1,50
Section width (mm)	246
Outer diameter of tyre [mm].	678
Stat. radius (SLR) [mm]	306
Rolling circumference [mm].	2042
Tread depth (mm)	26,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
56 M	224	130		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.