

## TYRES

|                 |               |
|-----------------|---------------|
| Product group   | Tyres         |
| Item number     | 12500579      |
| Valid tyre size | 255 / 70 R 12 |
| LI / SI / PR    | 58 J, 4 PR    |
| TL/TT           | TL            |
| Brand           | Carlisle      |
| Tread pattern   | A.C.T.        |



## Notes and features

- The Carlisle A.C.T. is an ATV radial tyre for particularly rough terrain with soft to medium-hard ground conditions.
- The radial casing compensates for hazards and path damage and provides high traction and ride comfort.
- The open tread pattern with high tread depth provides good self-cleaning and grip on muddy trails.
- The strong sidewall makes the tyre particularly puncture-proof.
- Tyres in HD model (Heavy Duty) have an even stronger casing to enable higher inflation pressures and loading capacities.

## Technical Informations

|                              |                    |
|------------------------------|--------------------|
| Item number                  | 12500579           |
| EAN                          | 5999110800561      |
| Valid tyre size              | 255 / 70 R 12      |
| Alternative size 1           | 26x10.00R12        |
| LI / SI / PR                 | 58 J, 4 PR         |
| TL/TT                        | TL                 |
| Brand                        | Carlisle           |
| Tread pattern                | A.C.T.             |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| ECE regulation number        | ECE 75             |
| Nettogewicht [kg] (gültig)   | 11,20              |
| Recommended rim size         | 8.0                |
| Permitted rim size           | 6.0, 7.0, 7.5, 8.5 |
| Maximum air pressure [bar].  | 0,70               |
| Section width (mm)           | 264                |
| Outer diameter of tyre [mm]. | 676                |
| Stat. radius (SLR) [mm]      | 303                |
| Rolling circumference [mm].  | 2022               |
| Tread depth (mm)             | 19,0               |
| E-Ready                      | No                 |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 58 J  | 236                | 100          |               | 0,70                     |              |