Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres	
Item number	12500580	
Valid tyre size	285 / 60 - 12	
LI / SI / PR	100 A4 / 96 A6, 4 PR	
TL/TT	TL	
Brand	Carlstar	
Tread pattern	Multi Trac C/S	



Notes and features

- Tyre for professional use on lawns, gardens and golf courses.
- Durable rubber compound in conjunction with deep tread blocks.
- Tread pattern optimised for stability and traction.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500580
EAN	5999110800011
Valid tyre size	285 / 60 - 12
Alternative size 1	26x12.00-12
LI / SI / PR	100 A4 / 96 A6, 4 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	Multi Trac C/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,60
Recommended rim size	8.50
Permitted rim size	8.0, 9.5, 10.5
Maximum air pressure [bar].	1,38
Section width (mm)	287
Outer diameter of tyre [mm].	648
Stat. radius (SLR) [mm]	289
Rolling circumference [mm].	1925
Tread depth (mm)	9,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
100 A4	800	20		1,38	
96 A6	710	30		1,38	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.