Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres
Item number	12500594
Valid tyre size	290 / 50 - 12
LI / SI / PR	109 A4, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Turf Trac R/S



Notes and features

- Lawn tyre for all kinds of devices for professional lawn and landscape maintenance.
- Wide range of applications from zero-turn rotary mowers to utility vehicles.
- Tread design effectively protects green spaces.
- High tread depth guarantees longevity.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500594
EAN	5999110828039
Valid tyre size	290 / 50 - 12
LI / SI / PR	109 A4, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Turf Trac R/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9,60
Recommended rim size	8.50
Maximum air pressure [bar].	2,20
Section width (mm)	285
Outer diameter of tyre [mm].	587
Stat. radius (SLR) [mm]	263
Rolling circumference [mm].	1750
Tread depth (mm)	8,6
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A4	1030	20		2,20	
	925	40		2,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.