

TYRES

Product group	Tyres	
Item number	12500689	
Valid tyre size	320 / 55 - 15	
LI / SI / PR	112 B, 10 PR	
TL/TT	TL	
Brand	Carlstar	
Tread pattern	Multi Trac C/S	



Notes and features

- Tyre for professional use on lawns, gardens and golf courses.
- Durable rubber compound in conjunction with deep tread blocks.
- Tread pattern optimised for stability and traction.



Technical Informations

Item number	12500689
EAN	5999110800172
Valid tyre size	320 / 55 - 15
Alternative size 1	29x12.50-15
LI / SI / PR	112 B, 10 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	Multi Trac C/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	18,00
Recommended rim size	10.00
Permitted rim size	10LB
Maximum air pressure [bar].	4,15
Section width (mm)	318
Outer diameter of tyre [mm].	737
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2291
Tread depth (mm)	8,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 B	1120	50		4,10	
	1344	25		4,15	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.