Bohnenkamp Moving Professionals

17.11.2024

TYRES

Product group	Tyres	
Item number	12500700	
Valid tyre size	360 / 50 - 15	
LI / SI / PR	99 B, 6 PR	
TL/TT	TL	
Brand	Carlstar	
Tread pattern	Ultra Trac	



Notes and features

- Special tyre for professional lawn and landscape maintenance.
- Offers very good flotation properties due to a flat contact area and reduced tread gaps.
- Low soil pressure and good traction at the same time.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500700
EAN	5999110802343
Valid tyre size	360 / 50 - 15
Alternative size 1	29x14.00-15
LI / SI / PR	99 B, 6 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	Ultra Trac
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	21,50
Recommended rim size	12.00
Permitted rim size	11LB, 12LB, 13LB
Maximum air pressure [bar].	2,10
Section width (mm)	366
Outer diameter of tyre [mm].	737
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2291
Tread depth (mm)	9,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
99 B	775	50		2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.