

TYRES

Product group	Tyres
Item number	12500900
Valid tyre size	250 / 60 - 8
LI / SI / PR	69 F, 4 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	All Trail II



Notes and features

- The Carlisle All Trail was specially designed for use on hard surfaces.
- Its low, wide tread pattern makes the vehicle very stable.
- The uniquely firm tread compound provides a very good ride comfort.
- Its rubber compound makes the tyre very durable and provides outstanding handling characteristics on pavement, concrete and compacted soil.

Technical Informations

Item number	12500900
EAN	5999110804507
Valid tyre size	250 / 60 - 8
Alternative size 1	20x10.00-8
LI / SI / PR	69 F, 4 PR
TL/TT	TL
Brand	Carlstar
Tread pattern	All Trail II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	6,20
Recommended rim size	8.0
Permitted rim size	7.0, 7.5, 8.5
Maximum air pressure [bar].	1,50
Section width (mm)	239
Outer diameter of tyre [mm].	503
Stat. radius (SLR) [mm]	224
Rolling circumference [mm].	1490
Tread depth (mm)	11,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
69 F	325	80		1,50	