Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	12510300
Valid tyre size	250 / 50 - 10
LI / SI / PR	86 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Rib



Notes and features

• Hay machine tyre with very robust casing.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12510300
EAN	5999110828206
Valid tyre size	250 / 50 - 10
Alternative size 1	20x10.00-10
LI / SI / PR	86 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Rib
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,40
Recommended rim size	6.00
Maximum air pressure [bar].	1,50
Section width (mm)	222
Outer diameter of tyre [mm].	508
Stat. radius (SLR) [mm]	227
Rolling circumference [mm].	1513
Tread depth (mm)	6,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
86 A4	530	20		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.