

TYRES

Product group	Tyres
Item number	12520109
Valid tyre size	280 / 60 - 12
LI / SI / PR	81 G, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	AT 489



Notes and features

- The Carlisle AT489 is one of Carlisle's top-selling ATV tyres.
- Its tread pattern with large distances between the lugs offers very good self-cleaning on any type of surface.
- The tyre is light, yet very robust and absorbs impacts reliably.
- Thanks to the rounded shoulders, it provides very good manoeuvrability and perfect cornering.



Technical Informations

Item number	12520109
EAN	5999110800790
Valid tyre size	280 / 60 - 12
Alternative size 1	25x11.00-12
LI / SI / PR	81 G, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	AT 489
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	9,70
Recommended rim size	8.0
Permitted rim size	8.5, 9.0
Maximum air pressure [bar].	0,82
Section width (mm)	272
Outer diameter of tyre [mm].	646
Stat. radius (SLR) [mm]	289
Rolling circumference [mm].	1930
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
81 G	462	90		0,82	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.