

TYRES

Product group	Tyres	
Item number	12520151	
Valid tyre size	215 / 65 D 14	
LI / SI / PR	106 A2, 6 PR	
TL/TT	TL	
Brand	Carlisle	
Tread pattern	Trac Chief	



Notes and features

- The Carlisle Trac Chief is a tyre for compact loaders, backhoe loaders and small tractors.
- The flat pattern with angled lugs enables high traction and stability.
- The reinforced sidewall and integrated rim guard prevent damage to the sidewall and bead area.



Technical Informations

Item number	12520151
EAN	5999110800509
Valid tyre size	215 / 65 D 14
Alternative size 1	25x8.50-14
LI / SI / PR	106 A2, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Trac Chief
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	13,00
Recommended rim size	7.00
Permitted rim size	7.00I, 7.00 I, 7JA
Maximum air pressure [bar].	3,45
Section width (mm)	213
Outer diameter of tyre [mm].	655
Stat. radius (SLR) [mm]	295
Rolling circumference [mm].	1958
Tread depth (mm)	13,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 A2	950	10		3,41	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.