

## **TYRES**

Product group	Tyres
Item number	12598018
Valid tyre size	24 x 13.00 B 12
LI / SI / PR	109 A4, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Ultra Trac



## Notes and features

- Special tyre for professional lawn and landscape maintenance.
- Offers very good flotation properties due to a flat contact area and reduced tread gaps.
- Low soil pressure and good traction at the same time.



## **Technical Informations**

Item number	12598018
EAN	5999110802732
Valid tyre size	24 x 13.00 B 12
Alternative size 1	320/45B12
LI / SI / PR	109 A4, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Ultra Trac
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	12,70
Recommended rim size	10.50
Permitted rim size	10.501
Maximum air pressure [bar].	1,93
Section width (mm)	327
Outer diameter of tyre [mm].	593
Stat. radius (SLR) [mm]	265
Rolling circumference [mm].	1766
Tread depth (mm)	6,9
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A4	1030	20		1,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.