

TYRES

Product group	Tyres
Item number	12598021
Valid tyre size	280 / 60 - 12
LI / SI / PR	82 F, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	All Trail II



Notes and features

- The Carlisle All Trail was specially designed for use on hard surfaces.
- Its low, wide tread pattern makes the vehicle very stable.
- The uniquely firm tread compound provides a very good ride comfort.
- Its rubber compound makes the tyre very durable and provides outstanding handling characteristics on pavement, concrete and compacted soil.

Technical Informations

Item number	12598021
EAN	5999110804606
Valid tyre size	280 / 60 - 12
Alternative size 1	25x11.00-12
LI / SI / PR	82 F, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	All Trail II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	9,50
Recommended rim size	9.0
Permitted rim size	8.0, 8.5, 9.5
Maximum air pressure [bar].	1,50
Section width (mm)	274
Outer diameter of tyre [mm].	648
Stat. radius (SLR) [mm]	288
Rolling circumference [mm].	1922
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
82 F	475	80		1,50	
	580	65		1,50	
	437	85		1,50	
	530	70		1,50	