

## **TYRES**

| Product group   | Tyres           |
|-----------------|-----------------|
| Item number     | 12598036        |
| Valid tyre size | 230 / 70 R 14   |
| LI / SI / PR    | 73 N, 6 PR      |
| TL/TT           | TL              |
| Brand           | Carlstar        |
| Tread pattern   | Versa Trail ATR |



## Notes and features

- The Carlisle Versa Trail ATR is a versatile ATV radial tyre for medium-hard and hard surfaces.
- The non-directional tread pattern provides excellent adaptability to any terrain and optimum traction with good ride comfort.
- Its strong rubber compound provides good protection against cuts and punctures and premature wear.
- This makes the tyre really resistant against punctures.



## **Technical Informations**

| Item number                  | 12598036        |
|------------------------------|-----------------|
| EAN                          | 5999110834849   |
| Valid tyre size              | 230 / 70 R 14   |
| Alternative size 1           | 27x9.00R14      |
| LI / SI / PR                 | 73 N, 6 PR      |
| TL/TT                        | TL              |
| Brand                        | Carlstar        |
| Tread pattern                | Versa Trail ATR |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 75          |
| Nettogewicht [kg] (gültig)   | 12,70           |
| Recommended rim size         | 7.0             |
| Permitted rim size           | 6.0, 6.5, 7.5   |
| Maximum air pressure [bar].  | 2,20            |
| Section width (mm)           | 226             |
| Outer diameter of tyre [mm]. | 693             |
| Stat. radius (SLR) [mm]      | 312             |
| Rolling circumference [mm].  | 2079            |
| Tread depth (mm)             | 19,0            |
| E-Ready                      | No              |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 73 N  | 365                | 140          |               | 2,20                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.