Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	13315320	
Valid tyre size	710 / 50 R 30.5	
LI / SI / PR	173 D	
TL/TT	TL	
Brand	Michelin	
Tread pattern	CargoXBib	



Notes and features

- Suitable for agricultural trailers and other towed vehicles. •
- High load capacity and large contact area.
- Exceptional handling and low rolling resistance.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13315320
EAN	3528700027860
Valid tyre size	710 / 50 R 30.5
LI / SI / PR	173 D
TL/TT	TL
Brand	Michelin
Tread pattern	CargoXBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	198,00
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	728
Outer diameter of tyre [mm].	1495
Stat. radius (SLR) [mm]	649
Rolling circumference [mm].	4408
Tread depth (mm)	21,0
Tyre capacity 75% [ltr.]	537
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.