

TYRES

Product group	Tyres
Item number	13326552
Valid tyre size	IF 320 / 85 R 38
LI / SI / PR	151 A8 / 151 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib RC



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Ideal for medium-performance tractors.
- Enormous traction with low soil compaction.
- Excellent ride comfort.
- Long service life due to very high tread lugs.

Technical Informations

Item number	13326552
EAN	3528703510970
Valid tyre size	IF 320 / 85 R 38
Alternative size 1	12.4R38
LI / SI / PR	151 A8 / 151 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib RC
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	85,00
Recommended rim size	DW11A
Permitted rim size	DW10A, W10, W11
Maximum air pressure [bar].	4,00
Section width (mm)	330
Outer diameter of tyre [mm].	1506
Stat. radius (SLR) [mm]	697
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4496
Tread depth (mm)	47,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	170
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		4,00	
151 B	3450	50		4,00	