

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 13326930 |
| Valid tyre size | VF 540 / 65 R 30 |
| LI / SI / PR | 158 D / 155 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | AxioBib 2 |



Notes and features

- The Michelin AxioBib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 13326930 |
| EAN | 3528702966389 |
| Valid tyre size | VF 540 / 65 R 30 |
| LI / SI / PR | 158 D / 155 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | AxioBib 2 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 145,00 |
| Recommended rim size | 18 |
| Permitted rim size | 16 |
| Maximum air pressure [bar]. | 2,00 |
| Section width (mm) | 545 |
| Outer diameter of tyre [mm]. | 1468 |
| Stat. radius (SLR) [mm] | 645 |
| Rolling circumference [mm]. | 4339 |
| Tread depth (mm) | 48,0 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 332 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 158 D | 4250 | 65 | | 2,00 | |
| 155 E | 3875 | 70 | | 2,00 | |