

TYRES

Product group	Tyres	
Item number	13327085	
Valid tyre size	VF 750 / 65 R 26 CFO +	
LI / SI / PR	180 A8	
TL/TT	TL	
Brand	Michelin	
Tread pattern	CerexBib 2	





Notes and features

- The Michelin Cerexbib 2 is a newly-developed tyre for large harvesting machines.
- Its contact area, which is up to 15% larger than that of the CerexBib, provides optimum soil protection.
- All Cerexbib 2 tyres are CFO tyres ans therefore suitable for cyclic field operations.
- The Cerexbib 2 has a special casing construction with Ultraflex technology.
- This casing design enables up to 40 higher loading capacities at the same inflation pressure for VF tyres.



Technical Informations

Item number	13327085
EAN	3528701322667
Valid tyre size	VF 750 / 65 R 26 CFO +
LI / SI / PR	180 A8
TL/TT	TL
Brand	Michelin
Tread pattern	CerexBib 2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	238,00
Recommended rim size	DW25B
Maximum air pressure [bar].	2,80
Section width (mm)	748
Outer diameter of tyre [mm].	1623
Stat. radius (SLR) [mm]	701
Rolling circumference [mm].	4786
Tread depth (mm)	48,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	659
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 A8	8000	40		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.