Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	13327270
Valid tyre size	IF 750 / 75 R 46
LI / SI / PR	186 D
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib



Notes and features

- Low fuel consumption due to very good traction.
- Low tyre inflation pressure even when under heavy load.
- High load capacity thanks to Ultraflex technology.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13327270
EAN	3528704870011
Valid tyre size	IF 750 / 75 R 46
LI / SI / PR	186 D
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	390,00
Recommended rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	761
Outer diameter of tyre [mm].	2287
Stat. radius (SLR) [mm]	1043
Rolling circumference [mm].	6819
Tread depth (mm)	71,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	1147
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
186 D	9500	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.