

## **TYRES**

Product group	Tyres
Item number	13327310
Valid tyre size	280 / 80 R 18
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



## Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.

- Solid lugs.
- Belt plies made from steel mesh.



## **Technical Informations**

Item number	13327310
EAN	3528707798039
Valid tyre size	280 / 80 R 18
Alternative size 1	10.5R18
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	43,00
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	4,00
Section width (mm)	290
Outer diameter of tyre [mm].	908
Stat. radius (SLR) [mm]	415
Rolling circumference [mm].	2708
Tread depth (mm)	28,0
Number of lugs	18x2
Lug width (mm)	36
Tyre capacity 75% [ltr.]	68
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40		4,00	
132 B	2000	50		4,00	