

TYRES

Product group	Tyres
Item number	13327323
Valid tyre size	400 / 70 R 18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.
- Solid lugs.
- Belt plies made from steel mesh.

Technical Informations

Item number	13327323
EAN	3528701330358
Valid tyre size	400 / 70 R 18
Alternative size 1	405/70R18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	64,00
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	4,00
Section width (mm)	397
Outer diameter of tyre [mm].	1012
Stat. radius (SLR) [mm]	451
Rolling circumference [mm].	2996
Tread depth (mm)	29,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	129
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		4,00	
147 B	3075	50		4,00	