

TYRES

Product group	Tyres
Item number	13327330
Valid tyre size	280 / 80 R 20
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.

- Solid lugs.
- Belt plies made from steel mesh.



Technical Informations

Item number	13327330
EAN	3528707474421
Valid tyre size	280 / 80 R 20
Alternative size 1	10.5R20
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	48,00
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	4,00
Section width (mm)	292
Outer diameter of tyre [mm].	958
Stat. radius (SLR) [mm]	439
Rolling circumference [mm].	2860
Tread depth (mm)	29,0
Number of lugs	18x2
Lug width (mm)	35
Tyre capacity 75% [ltr.]	73
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		4,00	
133 B	2060	50		4,00	