

TYRES

Product group	Tyres
Item number	13327340
Valid tyre size	340 / 80 R 20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.

- Solid lugs.
- Belt plies made from steel mesh.



Technical Informations

Item number	13327340
EAN	3528709487306
Valid tyre size	340 / 80 R 20
Alternative size 1	12.5R20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	62,00
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	4,00
Section width (mm)	353
Outer diameter of tyre [mm].	1047
Stat. radius (SLR) [mm]	476
Rolling circumference [mm].	3119
Tread depth (mm)	29,0
Number of lugs	19x2
Lug width (mm)	36
Tyre capacity 75% [ltr.]	114
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,00	
144 B	2800	50		4,00	