

TYRES

Product group	Tyres
Item number	13327350
Valid tyre size	380 / 75 R 20
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Bohnenkamp
■ ■ ■ Moving Professionals

Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.
- Solid lugs.
- Belt plies made from steel mesh.

Technical Informations

Item number	13327350
EAN	3528701877525
Valid tyre size	380 / 75 R 20
Alternative size 1	14.5R20
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	70,00
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	4,00
Section width (mm)	384
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	481
Rolling circumference [mm].	3180
Tread depth (mm)	33,0
Number of lugs	18x2
Lug width (mm)	36
Tyre capacity 75% [litr.]	136
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		4,00	
148 B	3150	50		4,00	