

TYRES

Product group	Tyres
Item number	13327356
Valid tyre size	400 / 70 R 20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Bohnenkamp
Moving Professionals



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.
- Solid lugs.
- Belt plies made from steel mesh.

Technical Informations

Item number	13327356
EAN	3528704744954
Valid tyre size	400 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	69,00
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	4,00
Section width (mm)	412
Outer diameter of tyre [mm].	1069
Stat. radius (SLR) [mm]	481
Rolling circumference [mm].	3177
Tread depth (mm)	33,0
Number of lugs	18x2
Lug width (mm)	37
Tyre capacity 75% [ltr.]	140
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	
149 B	3250	50		4,00	