

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 13327356 |
| Valid tyre size | 400 / 70 R 20 |
| LI / SI / PR | 149 A8 / 149 B |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | XMCL |



Bohnenkamp
Moving Professionals



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.
- Solid lugs.
- Belt plies made from steel mesh.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 13327356 |
| EAN | 3528704744954 |
| Valid tyre size | 400 / 70 R 20 |
| Alternative size 1 | 16.0/70R20 |
| LI / SI / PR | 149 A8 / 149 B |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | XMCL |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 69,00 |
| Recommended rim size | 13 |
| Permitted rim size | 12 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 412 |
| Outer diameter of tyre [mm]. | 1069 |
| Stat. radius (SLR) [mm] | 481 |
| Rolling circumference [mm]. | 3177 |
| Tread depth (mm) | 33,0 |
| Number of lugs | 18x2 |
| Lug width (mm) | 37 |
| Tyre capacity 75% [ltr.] | 140 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 149 A8 | 3250 | 40 | | 4,00 | |
| 149 B | 3250 | 50 | | 4,00 | |