

TYRES

Product group	Tyres
Item number	13327376
Valid tyre size	440 / 80 R 24
LI / SI / PR	161 A8 / 161 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL





Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.

- Solid lugs.
- Belt plies made from steel mesh.



Technical Informations

Item number	13327376
EAN	3528709547499
Valid tyre size	440 / 80 R 24
Alternative size 1	16.9R24
LI / SI / PR	161 A8 / 161 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	115,00
Recommended rim size	14
Permitted rim size	15
Maximum air pressure [bar].	4,00
Section width (mm)	441
Outer diameter of tyre [mm].	1314
Stat. radius (SLR) [mm]	592
Rolling circumference [mm].	3907
Tread depth (mm)	36,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	236
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		4,00	
161 B	4625	50		4,00	