

## **TYRES**

Product group	Tyres	
Item number	13327380	
Valid tyre size	460 / 70 R 24	
LI / SI / PR	159 A8 / 159 B	
TL/TT	TL	
Brand	Michelin	
Tread pattern	XMCL	



## Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.

- Solid lugs.
- Belt plies made from steel mesh.



## **Technical Informations**

Item number	13327380
EAN	3528702442685
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	101,00
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	4,00
Section width (mm)	467
Outer diameter of tyre [mm].	1248
Stat. radius (SLR) [mm]	562
Rolling circumference [mm].	3709
Tread depth (mm)	36,0
Number of lugs	18x2
Lug width (mm)	41
Tyre capacity 75% [ltr.]	218
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	