

TYRES

Product group	Tyres
Item number	13327395
Valid tyre size	540 / 70 R 24
LI / SI / PR	168 A8 / 168 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.
- Solid lugs.
- Belt plies made from steel mesh.

Technical Informations

Item number	13327395
EAN	3528709591287
Valid tyre size	540 / 70 R 24
Alternative size 1	21LR24
LI / SI / PR	168 A8 / 168 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	139,00
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	4,00
Section width (mm)	562
Outer diameter of tyre [mm].	1356
Stat. radius (SLR) [mm]	608
Rolling circumference [mm].	4026
Tread depth (mm)	38,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	317
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		4,00	
168 B	5600	50		4,00	