

TYRES

Product group	Tyres
Item number	13327422
Valid tyre size	480 / 80 R 26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.

- Solid lugs.
- Belt plies made from steel mesh.



Technical Informations

Item number	13327422
EAN	3528704259793
Valid tyre size	480 / 80 R 26
Alternative size 1	18.4R26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	132,00
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	4,00
Section width (mm)	495
Outer diameter of tyre [mm].	1422
Stat. radius (SLR) [mm]	635
Rolling circumference [mm].	4218
Tread depth (mm)	36,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	302
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		4,00	
167 B	5450	50		4,00	