

## TYRES

Product group	Tyres
Item number	13327460
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Bohnenkamp  
Moving Professionals



## Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Reinforced sidewalls.
- Solid lugs.
- Belt plies made from steel mesh.

## Technical Informations

Item number	13327460
EAN	3528703162230
Valid tyre size	440 / 80 R 28
Alternative size 1	16.9R28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	121,00
Recommended rim size	14
Permitted rim size	15
Maximum air pressure [bar].	3,20
Section width (mm)	459
Outer diameter of tyre [mm].	1410
Stat. radius (SLR) [mm]	641
Rolling circumference [mm].	4200
Tread depth (mm)	36,0
Number of lugs	22x2
Lug width (mm)	40
Tyre capacity 75% [ltr.]	260
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		3,20	
156 B	4000	50		3,20	