

TYRES

Product group	Tyres	
Item number	13327630	
Valid tyre size	540 / 65 R 30 143 D TL	
LI / SI / PR		
TL/TT		
Brand	Michelin	
Tread pattern	MultiBib	





Notes and features

- Up to 35% longer service life due to new rubber compound.
- Gentle on the soil due to flexible sidewalls.
- Good traction due to high lugs.
- State-of-the-art sidewall design with an appealing look.



Technical Informations

Item number	13327630
EAN	3528702231531
Valid tyre size	540 / 65 R 30
LI / SI / PR	143 D
TL/TT	TL
Brand	Michelin
Tread pattern	MultiBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	129,00
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	527
Outer diameter of tyre [mm].	1472
Stat. radius (SLR) [mm]	648
Rolling circumference [mm].	4353
Tread depth (mm)	48,0
Number of lugs	20x2
Lug width (mm)	45
Tyre capacity 75% [ltr.]	333
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 D	2725	65		1,60	