

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 13327630 |
| Valid tyre size | 540 / 65 R 30 |
| LI / SI / PR | 143 D |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | MultiBib |



Notes and features

- Up to 35% longer service life due to new rubber compound.
- Gentle on the soil due to flexible sidewalls.
- Good traction due to high lugs.
- State-of-the-art sidewall design with an appealing look.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 13327630 |
| EAN | 3528702231531 |
| Valid tyre size | 540 / 65 R 30 |
| LI / SI / PR | 143 D |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | MultiBib |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 129,00 |
| Recommended rim size | 16 |
| Permitted rim size | 18 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 527 |
| Outer diameter of tyre [mm]. | 1472 |
| Stat. radius (SLR) [mm] | 648 |
| Rolling circumference [mm]. | 4353 |
| Tread depth (mm) | 48,0 |
| Number of lugs | 20x2 |
| Lug width (mm) | 45 |
| Tyre capacity 75% [ltr.] | 333 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 143 D | 2725 | 65 | | 1,60 | |