# Bohnenkamp Moving Professionals

### **TYRES**

Product group	Tyres
Item number	13327835
Valid tyre size	VF 600 / 60 R 34
LI / SI / PR	149 D
TL/TT	TL
Brand	Michelin
Tread pattern	XeoBib



#### Notes and features

- Below 1 bar consistent low inflation pressure up to 65 km/h!
- Low soil compaction as a result.

- Saving fuel and time.
- High braking safety and steering precision.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	13327835
EAN	3528706647772
Valid tyre size	VF 600 / 60 R 34
LI / SI / PR	149 D
TL/TT	TL
Brand	Michelin
Tread pattern	XeoBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	158,50
Recommended rim size	20
Maximum air pressure [bar].	1,00
Section width (mm)	595
Outer diameter of tyre [mm].	1595
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4699
Tread depth (mm)	48,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	416
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 D	3250	65		1,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.