

TYRES

Product group	Tyres
Item number	13327850
Valid tyre size	VF 600 / 60 R 38
LI / SI / PR	151 D
TL/TT	TL
Brand	Michelin
Tread pattern	XeoBib



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Below 1 bar - consistent low inflation pressure up to 65 km/h!
- Low soil compaction as a result.
- Saving fuel and time.
- High braking safety and steering precision.

Technical Informations

Item number	13327850
EAN	3528703492573
Valid tyre size	VF 600 / 60 R 38
LI / SI / PR	151 D
TL/TT	TL
Brand	Michelin
Tread pattern	XeoBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	175,00
Recommended rim size	20
Maximum air pressure [bar].	1,00
Section width (mm)	586
Outer diameter of tyre [mm].	1698
Stat. radius (SLR) [mm]	749
Rolling circumference [mm].	5023
Tread depth (mm)	52,0
Number of lugs	20x2
Lug width (mm)	48
Tyre capacity 75% [ltr.]	452
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		1,00	