

TYRES

Product group	Tyres	
Item number	13327850	
Valid tyre size	VF 600 / 60 R 38	
LI / SI / PR	151 D	
TL/TT	TL	
Brand	Michelin	
Tread pattern	XeoBib	





Notes and features

- Below 1 bar consistent low inflation pressure up to 65 km/hl
- Low soil compaction as a result.

- Saving fuel and time.
- High braking safety and steering precision.



Technical Informations

Item number	13327850
EAN	3528703492573
Valid tyre size	VF 600 / 60 R 38
LI / SI / PR	151 D
TL/TT	TL
Brand	Michelin
Tread pattern	XeoBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	175,00
Recommended rim size	20
Maximum air pressure [bar].	1,00
Section width (mm)	586
Outer diameter of tyre [mm].	1698
Stat. radius (SLR) [mm]	749
Rolling circumference [mm].	5023
Tread depth (mm)	52,0
Number of lugs	20x2
Lug width (mm)	48
Tyre capacity 75% [ltr.]	452
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		1,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.