

TYRES

Product group	Tyres
Item number	13327980
Valid tyre size	VF 380 / 85 R 34
LI / SI / PR	149 B
TL/TT	TL
Brand	Michelin
Tread pattern	YieldBib



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Newly-developed tyre, especially for high-power tractors and self-propelled field sprayers used in row crops (corn, potatoes, etc.).
- Michelin Ultraflex Technology allows reduced inflation pressure by up to 40% with the same load capacity compared with standard radial tyres.
- Large contact area for reduced soil compaction and increased yield.
- Better traction due to R1W lugs with 45 degree lug angle enables reduced fuel consumption.
- Michelin Stubble Shield offers special protection against tread chunking and further impact damages caused by abrasive corn stubble.

Technical Informations

Item number	13327980
EAN	3528703054573
Valid tyre size	VF 380 / 85 R 34
LI / SI / PR	149 B
TL/TT	TL
Brand	Michelin
Tread pattern	YieldBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	105,00
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	1,60
Section width (mm)	386
Outer diameter of tyre [mm].	1510
Stat. radius (SLR) [mm]	668
Rolling circumference [mm].	4471
Tread depth (mm)	44,0
Tyre capacity 75% [ltr.]	229
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		1,60	
149 B	3250	50		1,60	